Ultra HD 4K digital signage player including NovoDS Studio software

to offer a full solution to create, publish and manage dynamic signage content for many applications.

NovoDS DS301 digital signage player offers outstanding 4K (@60fps) quality content to display digital signage in corporate or public spaces. Plug-and-play set up with easy remote management provide the basis for a quick start. Conveniently schedule content updates over the wired/wireless network or directly on the device using a microSD card.

NovoDS Studio (license free software included)

- Easy-to-manage software
- Fully customizable configuration

NovoDS Cloud (Optional)

- Enabling device and content management of NovoDS players over the Internet.

Features

- True 4K (4K @ 60fps) digital signage player with outstanding details and stunning visuals
- High performance web-browser engine (v.79 upgradeable) with excellent video decoding
- Display content directly from the built-in storage, microSD slot or USB flash drive
- Centralized remote management for deployment, monitoring and maintenance
- Compatible with Windows® and Mac® OS
- Software included to create, manage and publish digital signage content
- Kensington® security slot to prevent theft or movement of the device
- API integration

NovoDS DS301 Connectivity

Wi-Fi Antenna

RJ45 (Ethernet) · DC Power-In · HDMI-Out · Audio-Out · RS-232 3.5mm jack

MODEL	DS301
DISPLAY Resolutions	1280×720 (16:9 ,720P@60fps), 1920 x 1080 (16:9, 1080P@60fps), 3840 x 2160 (16:9, UHD@60fps)
Output Orientation	Portrait, Landscape
FEATURES Media Formats Supported	Images: JPEG, PNG, GIF, BMP, Video: MP2, MP4, H.264, VC-1 (WMV (Support up to 1080P@60FPS, UHD@30FPS) Audio: MP3, WMA, AAC
Software	NovoDS Studio, NovoDS Cloud
Security Solutions	AES-256 Encryption, Kensington® Security Slot
SOFTWARE NovoDS Studio Operating System Requirement	Windows® 7.0 and above, Mac® 10.7 and above)
NovoDS Cloud Supported Browsers	Google Chrome, Edge,Firefox,
CONNECTIVITY Wireless	WiFi: 802.11 b/g/n/ac (2.4GHz & 5GHz), 2T2R, Bluetooth V4.1
Input /Output Connection Ports	Input: USB2.0 Type A (x1), USB Type C (x1), microSD Slot, RS-232 (3.5mm), RJ45, Power Input (5V/3A), reset button
	Output: HDMI-Out v2.0 (HDCP v2.2 Compliant), Audio-Out (3.5mm)
	Internet (Ethernet): RJ45 (x1) (10/100/1000 Mbps)
SYSTEM Storage	Internal: 16GB (eMMC Flash) External: microSD Card Slot (Up to 32GB),USB Type A/C Flash Drive (Up to 32GB)
GENERAL Weight	296g (10.4oz)
LED Indicator	Green (System Power On), Red (System in Standby), Blue (Network Activity)
Accessories	AC Power Adapter (Depends on Region), USB Power Cable, HDMI Cable, Mounting Kit