

## **Specifications**

# **SMART Board® 7086 interactive display**

Model SBID-7086

## Overview

The SMART Board® 7086 interactive display combines a premium touch experience with the power of SMART Learning Suite, including SMART Notebook®, SMART lab™, SMART amp® and SMART response 2™ software.

The 86" 4K ultra-high-definition LED display provides optimal image clarity and wide viewing angles. With the Pen  $ID^{\infty}$  feature, you can assign different appearances to the four pens and write or draw over any application in digital ink.




Object Awareness<sup>™</sup> allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and four users can write or draw at the same time.

See education.smarttech.com for more information.

# Dimensions and weights<sup>1</sup>

#### **Dimensions**



#### Weight

205 lb. (91 kg)

#### Shipping dimensions (including pallet)

86 1/2" × 60" × 14"

(220 cm  $\times$  163 cm  $\times$  35.5 cm)

# Shipping weight

258 lb. (117 kg)

 $<sup>^1\!</sup>$  All dimensions  $\pm$  1/8" (0.3 cm). All weights  $\pm$  2 lb. (0.9 kg).

## Hardware

#### Interaction

Touch technology HyPr Touch™ (Hybrid Precision Touch) proprietary hybrid system, which greatly improves upon

its InGlass™ core by optimizing both touch and pen performance, resulting in virtually no lag and

zero contact detect height

Multitouch capabilities 16

Object Awareness Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger,

eraser or palm.

Pen ID Four people can write independently and simultaneously, using different colored ink.

Display

Type LED

Aspect ratio 16:9

Optimal resolution 3840 × 2160 at 60 Hz

Horizontal frequency

(typical)

135 kHz

Vertical frequency

(typical)

60 Hz

Contrast ratio (typical) 5000:1

Brightness (maximum) 360 cd/m<sup>2</sup>

Pixel dimensions 0.429 mm × 0.429 mm

Gamut 72% of NTSC

Viewing angle 178°

Response time (typical) 8 ms

**1000BASE-T Ethernet** Two external ports for a four-port Gigabit Ethernet switched network connecting the interactive

display and the OPS module to an external network and an external device, such as a

computer

Presence detection Dual sensors that reduce startup time and power consumption during inactivity

Audio 10 W integrated speakers (×2)

Noise level <30 dBA

Included cables and

accessories

Country-specific power cable

USB cable Pen (×4)

Eraser

**Mounting holes** For a standard VESA® 600 mm × 400 mm mounting plate

Lower mounting holes 17 1/8" (43.4 cm) from the bottom of the interactive display

Mounting bracket depth Minimum depth of 2" (5.1 cm) for all components on the back of the interactive display for airflow

# Connectors

Connector panel OPS slot

Stereo 3.5 mm out

S/PDIF out

VGA input connectors

VGA in

Stereo 3.5 mm in USB Type-B

**HDMI 1 input connectors** 

HDMI 2.0 in USB Type-B

Display Port input connectors

in

USB Type-B USB Type-A<sup>3</sup> RJ45 (×2)

Convenience panel HDMI 2 input connectors

HDMI 1.4 in USB Type-B USB Type-A (×2)

**Bottom** AC power in

AC power out RS-232 in RS-232 out

**HDCP support** Version 1.4/2.2

# Installation requirements

Interactive display See the SMART Board 7000 and 7000 Pro series interactive displays installation and

maintenance guide (smarttech.com/kb/171164)

# Room computers and guest laptops

General requirements See SMART Notebook software release notes

4K UHD Graphics card that can support  $3840 \times 2160$  resolution at 60 Hz and that has 1 GB DDR 5 memory

See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel

<sup>&</sup>lt;sup>3</sup>For service use only

## Mini-computers

General requirements See SMART Notebook software release notes

Dimensions Smaller than  $10" \times 10" \times 2"$  (25.4 cm  $\times$  25.4 cm  $\times$  5.1 cm)

Weight Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm  $\times$  75 mm or 100 mm  $\times$  100 mm mounting pattern

# Cable requirements

**HDMI** Maximum length: 23' (7 m)

#### **NOTES**

• Use only certified HDMI cables that have been tested to support the performance standard you require.

 The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.

**DisplayPort** DisplayPort 1.2 compliant or better

Maximum length: 23' (7 m)

**USB** Maximum length: 16' (5 m)

Important Using cables that exceed these maximum lengths can produce unexpected results, such as

degraded picture quality or USB connectivity. Refer to *SMART installation standards* (smarttech.com/kb/171035) for comprehensive information about cables and extensions for

SMART hardware products.

# Storage and operating requirements

Power requirements 100V to 240V AC, 50 Hz to 60 Hz

## Power consumption at 77°F (25°C)

Standby mode <2 W

Normal operating

(out-of-box)

172 W

Operating temperature 4

41-95°F (5-35°C)

Storage temperature

-4-140°F (-20-60°C)

Humidity

5–80% relative humidity, non-condensing

# Certification and compliance

Regulatory certification EU RED and LV Directives, ISED, cUL, FCC, UL, RCM, CITIC, TRA

# **Environmental compliance**

European Union REACH, RoHS, WEEE, Battery and Packaging

U.S. CONEG Packaging, California Prop 65

# Purchasing information

## Order number

SBID-7086 SMART Board 7086 interactive display with SMART Learning Suite

**Optional accessories** 

UGK-AM40-EDU iQ appliance for SMART Board 6000 and 7000 series interactive displays

WM-SBID-501 Fixed wall mount for SMART Board interactive displays

Other See smarttech.com/accessories

**Warranty** Three-year limited equipment warranty

Extended warranty

EWY1-SBID-7086 One-year warranty extension

EWY2-SBID-7086 Two-year warranty extension

smarttech.com/support smarttech.com/contactsupport

<sup>© 2017–2018</sup> SMART Technologies ULC. All rights reserved. SMART Board, SMART Notebook, SMART lab, SMART amp, SMART response 2, Pen ID, Object Awareness, HyPr Touch, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. IPhone, iPad, iPod touch and Safari are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play, Android and Chrome are trademarks of Google Inc. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 05/2018.